



Carrying Case

Includes:

- Fiber Optic Light Source
- Instruction Manual
- (3) AA Batteries (required for operation)
- (2) Cleaning Swabs
- Protective Carrying Case
- (2) SC/UPC Adapters
- (2) ST/UPC Adapters
- FC-LC/UPC Adapter (Singlemode Only)
- (2) FC/UPC Adapters

Provides a stable light source for singlemode and multimode fiber in 850/1300/1310/1550 nm wavelengths.

- Highly stable output power and wavelengths
- Four modulation outputs at 850/1300 nm multimode, 1310/1550 nm singlemode
- Intelligent backlight control reduces power consumption
- Auto-off function can be turned on or off
- Automatic wavelength detection function
- SC, ST, FC & FC-LC adapters included
- PC/UPC adapters included
- Color LCD Display
- Backside Kickstand

SPECIFICATIONS

WAVELENGTH (NM)	850 / 1300 / 1310 / 1550
SPECTRAL WIDTH (NM)	≤5
TYPICAL OUTPUT (dBm)	-7
STABILITY (dB, 15 MIN)¹	≤0.05
TYPICAL OUTPUT POWER ADJUSTABLE RANGE (dB)	-5~-12
MODULATION FREQUENCY (Hz)	CW, 270, 330, 1K, 2K
INTERFACE TYPE	FC/SC/ST/LC (UPC)
DISPLAY SIZE	2.4-inch LCD
POWER SUPPLY	1.5V* 3 AA alkaline batteries
AUTO-OFF (MIN)	10
CONTINUOUS WORKING HOURS (HR)²	≥25
OPERATING TEMPERATURE (C °)	-10~+60
STORAGE TEMPERATURE (C °)	-25~+70
DIMENSIONS	7.44" x 3.31" x 1.85" (189mm x 84mm x 47mm)
WEIGHT	0.64 lb (290 g)
UPC #	810053350195

MADE FOR LIFE